



主要参数 (MAJOR TECHNICAL CHARACTERISTICS)

| | |
|--|-------------------------------|
| 特性阻抗 (Impedance) | 50 Ω |
| 工作电压 (Voltage rating) | 250V (rms) |
| 频率范围 (Frequency range) | 0~3 GHz |
| 介质耐压 (Dielectric withstanding voltage) | 750V (rms) |
| 接触电阻 (Contact resistance) | 内导体 (Center contact) ≤ 5.0 mΩ |
| | 外导体 (Outer contact) ≤ 2.5 mΩ |
| 绝缘电阻 (Insulation resistance) | > 1000 MΩ |
| 机械耐久性 (Durability) | > 500 cycles |
| 包装方式 (The packing way) | 吸塑盒 Blister Box: 100 pcs/box |

| Limits unit: mm | A(±) | B(±) | C(±) | D(±) | E(±) | F(±) | SIGNATURE DATE 作成日期 | SH-Link® 深圳市思翰铭科技有限公司 RF 射频 Shenzhen Sihanming Technology Co., Ltd | | | |
|-----------------|------|------|------|------|------|------|---------------------|---|----------------------------|---------------------|---------------|
| | 0-6 | 0.03 | 0.05 | 0.08 | 0.10 | 0.15 | | 0.20 | DRAWN BY 伍远航 2017.11.27 | SCALE 比例 | WEIGHT 重量 (g) |
| 6-18 | 0.05 | 0.08 | 0.10 | 0.15 | 0.20 | 0.25 | CHECKED BY | ITEM NO 品号 | | PART DESCRIPTION 品名 | |
| 18-30 | 0.08 | 0.10 | 0.15 | 0.20 | 0.25 | 0.35 | | APPROVED BY | SH3.660.109 | | MCX-KWE |
| 30-50 | 0.10 | 0.15 | 0.25 | 0.25 | 0.30 | 0.50 | | | | | |
| 50-80 | 0.15 | 0.20 | 0.25 | 0.35 | 0.50 | 0.65 | | | | | |
| 80-120 | 0.20 | 0.25 | 0.30 | 0.50 | 0.65 | 0.80 | | | | | |
| 120-180 | 0.25 | 0.35 | 0.50 | 0.65 | 0.80 | 0.95 | | | | | |
| 180-250 | 0.35 | 0.50 | 0.65 | 0.95 | 0.95 | 1.15 | | | | | |

| NO | DESCRIPTION 描述 | MATERIAL 材质 | SPECIFICATION 规格 | QTY 数量 |
|----|---------------------|-------------|------------------|--------|
| 3 | Insulator 绝缘体 | PIFE 铁弗龙 | | 1 |
| 2 | Inner conductor 中心针 | BeCu 铍铜 | GOLD PLATED 镀金 | 1 |
| 1 | Body 壳体 | Brass 黄铜 | GOLD PLATED 镀金 | 1 |