

					Limits unit:mm	A(±)	B(±)	C(±)	D(±)	E(±)	F(±)	SIGNATURE DATE作成日期		SH-Link [®] 深圳市思翰铭科技有限公司 XF 鑫泰 Shenzhen Sihanning Technology Co.,Ltd			
						0-6	0.03	0.05	0.08	0.10	0.15	0.20	DRAWN BY 陈南荣 2019.09.20	SCALE 比例	WEIGHT 重量(g)	PERSPECTIVE 视角方法	
						6-18	0.05	0.08	0.10	0.15	0.20	0.25					
						18-30	0.08	0.10	0.15	0.20	0.25	0.30					
						30-50	0.10	0.15	0.20	0.25	0.30	0.50	CHECKED BY	ITEM NO品号		PART DESCRIPTION品名	
						50-80	0.15	0.20	0.25	0.35	0.50	0.65					
						80-120	0.20	0.25	0.30	0.50	0.65	0.80					
3	Insulation 绝缘子	PIPE 聚四氟乙烯		1		120-140	0.25	0.35	0.50	0.65	0.80	0.95	APPROVED BY	SH3. 650. 1325		MMCX -JE-2	
2	Pin contact 中心针	Phosphor bronze 磷青铜	Gold plating镀金	1		150-250	0.35	0.50	0.65	0.75	0.90	1.15					
1	Hood外壳	Brass黄铜	Gold plating镀金	1													
NO	DESCRIPTION 描述	MATERIAL 材质	SPECIFICATION 规格	QTY数量													