



RECOMMENDED PCB LAYOUT

PERFORMANCE:

1. IMPEDANCE: 50 OHM
2. FREQUENCY RANGE: DC~ 40 GHZ
3. VSWR: DEPENDS ON PCB STACK-UP,
4. INSERTION LOSS: 0.1 X SQRT<F IN GHZ>>
5. DIELECTRIC WITHSTAND VOLTAGE: 325 VRMS.
6. OPERATING TEMPERATURE: -55 C° TO +125 C°

			Dimension: MM			SH-Link® 深圳市思翰铭科技有限公司 RF 射频 Shenzhen Sihanming Technology Co.,Ltd			
CENTER CONTACT	BERYLLIUM COPPER	GOLD	General tolerance Unless Otherwise Specified 0 Places: ±0.1 1 Places: ±0.05 2 Places: ±0.03 3 Places: 4 Places: Angles:			SCALE 比例	WEIGHT 重量(g)	PERSPECTIVE 视角方法	
DIELETRIC	PEEK OR PAI	NATURAL							
BODY	BRASS	GOLD				ITEM NO品号	PART DESCRIPTION品名		
DESCRIPTION	MATERIAL	FINISH				SHM-DJ2S-BE00	SMP PLUG, LIMITED DETENT, FOR PCB SURFACE MOUNT		